

AFROKING Gear Oil SAE 90 · 4 L

Product information and typical properties

AFROKING Gear Oil SAE 90 is an automotive gear lubricant supplied in the grade shown on the pack. The range includes clearly identified viscosity grades and pack sizes for workshop and fleet supply.

Applications

Use in gear systems only where the equipment manufacturer specifies the viscosity grade and performance designation shown on this pack.

Reference properties

Physical Properties			
Test Parameters	Test Methods	Units	Results
Appearance	Visual	NONE	Bright & Clear
Density @ 15°C	ASTM D1298	g/cm ³	0.89
Kinematic Viscosity @ 40°C	ASTM D445	cSt	198
Kinematic Viscosity @ 100°C	ASTM D445	cSt	17.8
Viscosity Index	ASTM D 2270	NONE	98
Flash Point	ASTM D 92	°C	232
Pour Point	ASTM D 97	°C	-21
API Performance Level	NONE	NONE	GL-4

Reference basis

Values reproduced from the corresponding Solar Lubricants product, based on the company's confirmation of equivalent specifications. This is a technical reference, not a batch certificate, product approval or safety data sheet. Packaging and branding differ.

[View the source product at Solar Lubricants](#)

For current product availability and safety documentation, contact AFROKING. www.afroking.sd